according to 1907/2006/EC, Article 31; (EU) 2015/830

Printing date 26.01.2021

Version number 16

Revision: 26.01.2021

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- 1.1 Product identifier
- Trade name Jowatherm Reaktant 608.00
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
 - · Application of the substance / the mixture Adhesives
 - · Uses advised against Restricted to professional users.
- 1.3 Details of the supplier of the safety data sheet
 - Manufacturer/Supplier: Jowat SE Ernst-Hilker-Str. 10 - 14; D - 32758 Detmold Fon +49 (0)5231 749 0 e-mail: info@jowat.de www.jowat.de Department issuing data specification sheet:
 - Environmental management Tel. +49 5231 749 -218 / -211 / -5460 / -5374 e-mail: umweltmanagement@jowat.de
 - Department providing the information: Jowat UK Ltd.
 - Lymedale Business Centre Lymedale Business Park Hooters Hall Road Newcastle-under-Lyme Staffordshire ST5 9QF Phone: +44 1782 565265
- E-mail: nick.orton@jowat.co.uk • **1.4 Emergency telephone number:** InfraServ Hoechst - Gefahrenabwehrmeldezentrale D - 65926 Frankfurt Fon: +49 (0)69-305-6418
- **SECTION 2: Hazards identification**
- [•] 2.1 Classification of the substance or mixture
 - Classification according to Regulation (EC) No 1272/2008



Resp. Sens. 1H334May cause allergy or asthma symptoms or breathing difficulties if inhaled.Carc. 2H351Suspected of causing cancer.



Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

according to 1907/2006/EC, Article 31; (EU) 2015/830

Printing date 26.01.2021

Version number 16

Revision: 26.01.2021

Trade name Jowatherm Reaktant 608.00

(Contd. from page 1)



Hazard pictograms

· Signal word Danger

- Hazard-determining components of labelling:
- diphenylmethane diisocyanate
- Hazard statements
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

Precautionary statements

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312 Call a doctor if you feel unwell.
- P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
- P501 Dispose of contents / container to approved waste disposal or recycling in accordance with national regulations.

• Additional information:

Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards

- Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• **Description:** Hot melt adhesive Polyurethane resin

· Dangerous components:

Bungerous components.		
CAS: 26447-40-5	diphenylmethane diisocyanate	1-<5%
EINECS: 247-714-0	Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373;	
registration number:	Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin	
01- 2119457024-46	Sens. 1, H317; STOT SE 3, H335	
01-2119457015-45-0001	Specific concentration limits: Skin Irrit. 2; H315: $C \ge 5$ %	
	Eye Irrit. 2; H319: C ≥ 5 %	
	Resp. Sens. 1; H334: C ≥ 0.1 %	
	STOT SE 3; H335: C ≥ 5 %	

• **SVHC** Not applicable.

Additional information

If any R-phrases (risk-phrases) are listed, please refer for the exact wording to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information

Instantly remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation

Supply fresh air and contact physician for safety reasons.

according to 1907/2006/EC, Article 31; (EU) 2015/830

Printing date 26.01.2021

Version number 16

(Contd. from page 2)

Trade name Jowatherm Reaktant 608.00

In case of unconsciousness bring patient into stable side position for transport.

Supply fresh air; consult physician in case of symptoms.

After skin contact

After contact with the molten product, cool rapidly with cold water.

Do not pull solidified product away from the skin.

Seek medical treatment.

- · After eye contact Rinse opened eye for several minutes under running water.
- · After swallowing In case of persistent symptoms consult physician.
- 4.2 Most important symptoms and effects, both acute and delayed Asthma attacks

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

- · For safety reasons unsuitable extinguishing agents Water with a full water jet.
- 5.2 Special hazards arising from the substance or mixture

Can be released in case of fire Nitrogen oxides (NOx) Carbon monoxide (CO) Hydrogen cyanide (HCN) **5.3 Advice for firefighters**

Protective equipment: Put on breathing apparatus.

Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.
- · 6.2 Environmental precautions: No special measures required.
- 6.3 Methods and material for containment and cleaning up: Dispose of contaminated material as waste according to item 13. Collect mechanically.
 Allow to solidify. Collect mechanically.
 Ensure adequate ventilation.
- 6.4 Reference to other sections
- See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment. See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Thorough dedusting.

Store in cool, dry place in tightly closed containers.

Ensure that suitable extractors are available on processing machines. In the context of the risk

assessment, it is necessary to evaluate whether and to what extent protective measures are required. If necessary, a workplace measurement has to be carried out.

· Information about protection against explosions and fires: Keep breathing equipment ready.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage
- Requirements to be met by storerooms and containers: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Store under dry conditions.
- Protect from humidity and keep away from water.
- · Storage class 11

Printing date 26.01.2021

Version number 16

Revision: 26.01.2021

Trade name Jowatherm Reaktant 608.00

· Explosive properties:

• 7.3 Specific end use(s) No further re	(Contd. from page 3)			
SECTION 8: Exposure contro				
SECTION 8. Exposure contro	is/personal protection			
 • 8.1 Control parameters • Components with critical values that require monitoring in the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace. • Additional information: The lists that were valid during the compilation were used as basis. 				
 Personal protective equipment General protective and hygienic Standard precautionary measures Keep away from food, beverages Instantly remove any soiled and ir Wash hands during breaks and a Store protective clothing separate Vacuum clean contaminated cloth Do not inhale gases / fumes / aero Avoid skin contact with the liquefic Do not eat or drink while working. Breathing equipment: 	a for handling chemicals are to be observed. and animal feed. npregnated garments. the end of work. ly. ing. Do not blow or brush off contamination. osols. ed material.			
SECTION 9: Physical and che	emical properties			
 9.1 Information on basic physical a General Information Appearance: Form: Colour: Smell: Odour threshold: 	nd chemical properties Solid. According to product specification Characteristic Not determined.			
· pH-value:	Not applicable.			
• Change in condition • Melting point/freezing point: • Initial boiling point and boiling	65 °C range: Not determined			
· Flash point:	>200 °C			
· Inflammability (solid, gaseous)	Product is not inflammable.			
· Ignition temperature:	520 °C			
· Decomposition temperature:	> 250 °C			
· Spontaneous combustion:	Product does not undergo spontaneous combustion.			

Product is not explosive.

Printing date 26.01.2021

Version number 16

Revision: 26.01.2021

Trade name Jowatherm Reaktant 608.00

		(Contd. from page
· Critical values for explosion:		
· Lower:	Not determined.	
· Upper:	Not determined.	
· Vapour pressure:	Not applicable.	
	< 0,01 hPa	
· Density at 20 °C	1.1 g/cm ³	
Relative density	Not determined.	
· Vapour density	Not applicable.	
 Evaporation rate 	Not applicable.	
 Solubility in / Miscibility with 		
· Water:	Unsoluble	
· distribution ratio (n-octanol/water):	Not determined.	
· Viscosity:		
· dynamic:	Not applicable.	
· kinematic:	Not applicable.	
· Solvent content:		
· Solid content:	100.0 %	
• 9.2 Other information		
· VOC - Volatile Organic Compounds		
 European Union 	0.00 %	
 Switzerland 	0.00 %	
· U.S.A (less water and less exemp	ots) 0.0 g/l / 0.00 lb/gal	
SECTION 10: Stability and react	ivity	
• 10.1 Reactivity No further relevant inform	-	
• 10.2 Chemical stability		
• Thermal decomposition / conditions	to be avoided [.]	
No decomposition if used according to		
To avoid thermal decomposition do not		
10.3 Possibility of hazardous reactions		
Toxic fumes may be released if heated a		

Toxic fumes may be released if heated above the decomposition point Reacts with water

Reacts with moist air

• **10.4 Conditions to avoid** No further relevant information available.

• **10.5 Incompatible materials:** No further relevant information available.

10.6 Hazardous decomposition products:

Nitrous vitriol gases Hydrogen cyanide (prussic acid) Isocyanate Inflammable gases/vapours Carbon monoxide and carbon dioxide Danger of toxic pyrolysis products Nitrogen oxides (NOx)

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity

Harmful if inhaled.

· LD/LC50 values that are relevant for classification:

Inhalative LC50 / 4 h 12 mg/l (rat)

according to 1907/2006/EC, Article 31; (EU) 2015/830

Printing date 26.01.2021

Version number 16

Revision: 26.01.2021

Trade name Jowatherm Reaktant 608.00

(Contd. from page 5)

26447-40-5 diphenylmethane diisocyanate			thane diisocyanate
	Oral	LD50 oral	10000 mg/kg (rat)
	Dermal	LD50 dermal	10000 mg/kg (rabbit)
Primary irritant effect:			ect:

• to the skin: Based on available data, the classification criteria are not met.

• to the eye: Based on available data, the classification criteria are not met.

· Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Additional toxicological information:

• CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity
- Suspected of causing cancer.

• Reproductive toxicity Based on available data, the classification criteria are not met.

- **STOT-single exposure** Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity:

26447-40-5 diphenylmethane diisocyanate

LC0 >1000 mg/l (zebrafish)

EC50 / 24 h >1000 mg/l (water flea)

EC50 / 3 h >100 mg/l (pseudomonas putida)

• 12.2 Persistence and degradability No further relevant information available.

• 12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

Do not allow the product to reach ground water, open water or the sewer system, undiluted or in large quantites.

12.5 Results of PBT and vPvB assessment

- · **PBT:** Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation Hand over to disposers of hazardous waste.

· Uncleaned containers/packaging material:

- · Recommendation:
- Non contaminated packagings can be reused.
- Non contaminated packagings can be used for recycling.
- Packaging with cured adhesive residues can be recycled.

Packaging with cured adhesive residues can be treated as household waste.

SECTION 14: Transport information

· 14.1 UN-Number · ADR, ADN, IMDG, IATA

not applicable

Printing date 26.01.2021

Version number 16

Revision: 26.01.2021

Trade name Jowatherm Reaktant 608.00

		(Contd. from page 6)
14.2 UN proper shipping name ADR	not applicable not applicable	
· ADN, IMDG, IATA	not applicable	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	not applicable	
14.4 Packing group ADR, IMDG, IATA	not applicable	
· 14.5 Environmental hazards:	Not applicable.	
· 14.6 Special precautions for user	Not applicable.	
 14.7 Transport in bulk according to Ann Marpol and the IBC Code 	nex II of Not applicable.	
· UN "Model Regulation":	not applicable	

SECTION 15: Regulatory information

\cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

These data are based on our present knowledge. They shall, however, not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. All standard industrial precautions apply, concerning protection of health, and safe handling. The recommendations have to be examined in the context of the application for which the product is intended,

and observed as necessary. · Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Printing date 26.01.2021

Version number 16

Revision: 26.01.2021

Trade name Jowatherm Reaktant 608.00

 \cdot * Data modified in comparison to the previous version.

(Contd. from page 7)

(Contd. on page 9)

according to 1907/2006/EC, Article 31; (EU) 2015/830

Printing date 26.01.2021

Version number 16

Revision: 26.01.2021

Trade name Jowatherm Reaktant 608.00

(Contd. from page 8)

Annex: Exposure scenario 1

Process category

PROC14 Tabletting, compression, extrusion, pelletisation, granulation

PROC21 Low energy manipulation and handling of substances bound in/on materials or articles Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

• **Conditions of use** Customary application according to section 1.

• **Duration and frequency** 8hrs (full working shift).

Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

· Concentration of the substance in the mixture The substance is main component.

· Used amount per time or activity 33333 tons per day

Other operational conditions Observe the standard safety regulations when handling chemicals Other operational conditions affecting environmental exposure

The product must not get in contact with soil, surface water and ground water before complete hardening.

Observe section 6 of the Safety Data Sheet (Accidental release measures).

High temperatures promote emission.

Other operational conditions affecting worker exposure

Avoid long-term or repeated skin contact.

Avoid contact with the skin and eyes.

Respiratory protection is required in work areas with inadequate ventilation and during spraying application.

Ensure adequate ventilation, especially in closed rooms.

Avoid contact with eyes.

Avoid contact with the skin.

Avoid breathing particles.

- · Other operational conditions affecting consumer exposure No special measures required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.

Risk management measures

Worker protection

Instantly remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· Organisational protective measures Provide Internal Plant Instruction.

· Technical protective measures

Ensure that suitable extractors are available on processing machines. In the context of the risk assessment, it is necessary to evaluate whether and to what extent protective measures are required. If necessary, a workplace measurement has to be carried out.

Personal protective measures

Use breathing protection in case of insufficient ventilation (EN 149).

Use breathing protection in case of insufficient ventilation (EN 14387). Filter A/B/P2.

In case of brief exposure or low pollution use breathing filter apparatus (EN 136). In case of intensive or longer exposure use breathing apparatus that is independent of circulating air (EN 137). Heat resistant gloves

Impervious gloves (EN 374).

· Measures for consumer protection Ensure adequate labelling.

Environmental protection measures

· Air No special measures required.

- Water Do not allow to reach sewage system.
- · Soil No special measures required.

Notes In case of unintended release of the product: See section 6 of the Safety Data Sheet.

· Disposal measures Ensure that waste is collected and contained.

according to 1907/2006/EC, Article 31; (EU) 2015/830

Printing date 26.01.2021

Version number 16

Revision: 26.01.2021

(Contd. from page 9)

Trade name Jowatherm Reaktant 608.00

· Disposal procedures

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Waste type

Partially emptied and uncleaned packaging

Solid product residues

- Exposure estimation
- · Worker (oral) No significant oral exposure

· Worker (dermal) No significant dermal exposure

- Worker (inhalation) The calculated value is smaller than the DNEL.
- Environment The calculated value is smaller than the PNEC.
- · Consumer Not relevant for this Exposure Scenario.

• Guidance for downstream users No further relevant information available.

(Contd. on page 11)

according to 1907/2006/EC, Article 31; (EU) 2015/830

Version number 16

Revision: 26.01.2021

Trade name Jowatherm Reaktant 608.00

(Contd. from page 10)

Annex: Exposure scenario 2

- · Sector of Use
- SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Process category
- PROC11 Non industrial spraying
- PROC14 Tabletting, compression, extrusion, pelletisation, granulation
- PROC21 Low energy manipulation and handling of substances bound in/on materials or articles Environmental release category
- ERC8c Widespread use leading to inclusion into/onto article (indoor)
- ERC8f Widespread use leading to inclusion into/onto article (outdoor)
- Description of the activities / processes covered in the Exposure Scenario
- See section 1 of the annex to the Safety Data Sheet.
- · Conditions of use Customary application according to section 1.
 - Duration and frequency 8hrs (full working shift).
 - · Worker 8hrs (full working shift).
- · Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

- Physical state Solid.
- Concentration of the substance in the mixture The substance is main component.
- Used amount per time or activity 8000 kg per day
- Other operational conditions Observe the standard safety regulations when handling chemicals Other operational conditions affecting environmental exposure
 - Observe section 6 of the Safety Data Sheet (Accidental release measures).

The product must not get in contact with soil, surface water and ground water before complete hardening.

- High temperatures promote emission.
- Other operational conditions affecting worker exposure
- Indoor application.

Outdoor application.

Avoid contact with eves.

Avoid contact with the skin.

Avoid long-term or repeated skin contact.

Avoid breathing particles.

- Other operational conditions affecting consumer exposure Not required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.

Risk management measures

Worker protection

Instantly remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · Organisational protective measures Provide Internal Plant Instruction.
- Technical protective measures

Ensure that suitable extractors are available on processing machines. In the context of the risk assessment, it is necessary to evaluate whether and to what extent protective measures are required. If necessary, a workplace measurement has to be carried out.

Personal protective measures

Use breathing protection in case of insufficient ventilation (EN 149). Filter A/B/P2.

In case of brief exposure or low pollution use breathing filter apparatus (EN 136). In case of intensive or longer exposure use breathing apparatus that is independent of circulating air (EN 137). Heat resistant gloves

Impervious gloves (EN 374).

· Measures for consumer protection Ensure adequate labelling.

· Environmental protection measures No special measures required.

Air No special measures required.

according to 1907/2006/EC, Article 31; (EU) 2015/830

Printing date 26.01.2021

Version number 16

Revision: 26.01.2021

(Contd. from page 11)

Trade name Jowatherm Reaktant 608.00

• Water Do not allow to reach sewage system.

· Soil No special measures required.

Notes In case of unintended release of the product: See section 6 of the Safety Data Sheet.

· Disposal measures Ensure that waste is collected and contained.

· Disposal procedures

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Waste type

Solid product residues

Partially emptied and uncleaned packaging

Exposure estimation

- · Worker (oral) No significant oral exposure
- Worker (inhalation) The calculated value is smaller than the DNEL.
- Environment The calculated value is smaller than the PNEC.
- · Consumer Not relevant for this Exposure Scenario.

· Guidance for downstream users No further relevant information available.